



REELSTRONG®

UTILITY FLEET

Reel, Pole and Gas Trailers using ACME-Clamp™, Safelock™, and Securelock™ Technologies



BASE MODEL W/ DUAL HAND PUMPS FOR UNEVEN TERRAIN



LOADED MODEL w/ SELF-CONTAINED PAYOUT

GR8K SERIES POWERLOCK™ REEL TRAILER SPECIFICATIONS

Exclusive Standard Added Value:

- POWERLOCK™ Technology provides industry leading safety, ease of use, low maintenance, and durability.
- SAFETY and Peace Of Mind
- No pins, cotters, or laynards that secure the reel arbor (which is the most critical safety point)
- Faster reel loading, unloading, and deployment reduce labor costs and fatigue on workers

BUILT FOR SAFETY. BUILT FOR SPEED. *BUILT TO LAST.*

GR8K SERIES POWERLOCK™ REEL TRAILER SPECIFICATIONS

GENERAL SPECIFICATIONS

- GVWR • 11,000 lbs. (De-Rateable)
- REEL DIAMETER • 125" Maximum
- REEL OPENING • 64" Approx.
- OVERALL WIDTH • 102" Approx.
- REEL WEIGHT • 8,500 lbs.
- OVERALL LENGTH • 137" Approx.
- TIRES • (2) 215/75 R17.5 (Load Range H)
- WHEELS • (2) 17.5 x 6.5 HC / 8 on 6.5 BC w/ .19 OFFSET
- BRAKES • 12.25" x 4" Electric w/ Safety Breakaway Kit
- AXLE • 10,000 lbs.
- REEL SHAFT DIAMETER • 2.5" Solid w/ Centering Collars
- HITCH • 3-Position 2.5" ID 4-Bolt Drawbar w/ GR8 Bolts
- SAFETY CHAINS • (2) 3/8" x 36" Long Grade 43 Zinc-Plated
- FENDERS • 1/8" Diamond Plate
- JACK • 7K Side-Wind Drop Leg

STANDARD FEATURES

- POWERLOCK™ Technology provides industry leading safety, ease of use, low maintenance, and durability.
- Auto-locking Swing Out Reel Bar Retainer
- FMVSS / CMVSS Standard 108 LED Lighting
- Rear Red Clearance Lights

- All specifications/designs subject to change without notice - All GVWR's & reel capacities are de-ratable to your needs

GR8K SERIES POWERLOCK™ REEL TRAILER SPECIFICATIONS

STANDARD FEATURES

(continued)

- Front Amber Clearance Lights
- All Lights Sealed & Grommet Mounted
- DOT Reflective Tape (Conspicuity Tape)
- Paint
 - I.M.P.A.C.T.
Intense Metal pH ACID Cleaning Technology
 - Hydrofluric, Sulfuric, Phosphoric ACID Bath
 - Seams Caulked
 - Rust Preventative 2-Part Epoxy Primer
 - 2-Part Polyurethane Top Coats
 - Standard Colors: Red, Black, White, and CAT Yellow

OPTIONS

- 3-Step Hot Dip Galvanizing (Includes 10 Year Structural Warranty)
- 12V Electric over Hydraulics w/ Solar Panel and Trickle Charger
- Fiber-Optic Cable Puller and Collapsible Reel Packages (Condux or GMP) with 11HP Engine (Honda)
- Hydraulic Take-up Retriever (Rim Drive)
- Hydraulic Power Pack (11HP Honda)
- 9" Overspin Brake
- Toolbox
- Engine Cover
- Rubber or All Weather Grip Strut Wheel Chocks
- All Stainless Fasteners