



REELSTRONG[®]

UTILITY FLEET

Reel, Pole and Gas Trailers using ACME-Clamp™, Safelock™, and
Securelock™ Technologies

LA-ACME CLAMP HD SELF LOADING CABLE PLACER **SPECIFICATIONS**



REELSTRONG UTILITY FLEET

283 South Oak Street

Manheim, PA 17545

Phone: 484.889.8048 • Fax: 888.380.3932

www.REELSTRONGUFLEET.com

BUILT FOR SAFETY. BUILT FOR SPEED. *BUILT TO LAST.*

LA ACME-CLAMP™ HD Self-Loading Cable Placer Specifications

Superior Added Value:

ACME-Clamp™ Technology Provides Industry Leading Safety, Ease of Use, Low Maintenance & Durability
Arborless Clamping Ars that Lower and Clamp onto Reel for the Safest, Fastest Least Back-Breaking Design in the Industry. No Heavy Reel Bar
Lower Center of Gravity to Prevent Trailer Flipping Over

Specifications:

Payloads: 16K & 20K lbs.

Reel Diameter: 108" or 120"

Reel Opening: 68"

Overall Width: 102"

Reel Weight: 20,000

Overall Length: 187" Approx.

Axles: Dexter Axles

- (2) 12K Tandem Axles, 26,400 GVWR@10% Tongue Wt.
- (2) 15K Tandem Axles, 33,000 GVWR@10% Tongue Wt.
- (3) 12K Tandem Axles, 39,000 GVWR@10% Tongue Wt.
- (3) 15K Tandem Axles, 49,500 GVWR@10% Tongue Wt.
- Tires: 235/75 R17.5 (Load Range H)
- Wheels: 17.5x6.75 HC / 8 on 6.5 BC w/ .50 Outset

Standard Features:

Hitch: 6-position 28K Pintle

Safety Chains: (2) 1/2" Grade 70 Zinc-Plated

Fenders: 1/8" Diamond Plate

Jack: 12K Side-Wind Drop Leg

Grounding Lug: 5/8" Copper Coated / Welded to Frame

ACME-Clamp™ Technology provides Industry Leading Safety, Ease of Use, Low Maintenance & Durability
Wheel Chock Holders
Telescoping Hydraulic Outriggers

Note: All Specifications / Designs are subject to change without notice - All GVWR's & reel capacity are de-ratable to your needs.

LA ACME-CLAMP™ HD Self-Loading Cable Placer

Specifications

Standard Features (Cont):

- Plug & Play Wiring Harness
- DOT Conspicuity Reflective Tape
- All Lights Sealed and Grommet Mounted
- Rear Red Marker Lights, Amber Clearance Lights
- FMVSS/CMVSS Standard 108 LED Lighting

Paint:

- I.M.P.A.C.T. Intense Metal pH Acid Cleaning Technology
- Hydrofluoric, Sulfuric, Phosphoric ACID BLEND CLEANING PREP.
- Seams Caulked I.M.P.A.C.T. Intense Metal pH Acid Cleaning Technology
- Rust Preventative 2-Part Epoxy Primer
- Standard Colors Red, Black, White & CAT Yellow

Options

- Air Brakes
- Wheel Chocks: Rubber or All Weather Galvanized Grip Strut
- Solar Charged Breakaway Kit
- Optional: 3-Step Hot Dip Galvanizing (includes 10 year Structural Warranty)
- 16" or 24" Tension Brake
- Heavy Duty Composite Outrigger Pads
- 3300, 3900 ft/lbs Take-Up Retriever
- 16" or 24" Ventilated Tension Brake
- Self-Propelled Mechanism
- Engine Cover
- Aluminum Toolbox
- All Stainless Fasteners
- 110 VAC Generator, 12VDC 500 Watt

Note: All Specifications / Designs are subject to change without notice - All GVWR's & reel capacity are de-ratable to your needs.